

		
<p>1) Tools needed: Glass cleaner, razor blade or scissors, squeegee, tape measure, needle, masking tape and a friend to help.</p>	<p>2) Clean entire surface of vehicle thoroughly make sure it's free from oil and wax. Place the decal in the glass and start measuring to center and to even the decal out, use the masking tape to hold in place. When your satisfied with the position place a long vertical masking tape on the center of the decal. Make sure this is attached good.</p>	<p>3) Remove the the small tape holding the decal on, <b>Not</b> the long vertical on the center. Slowly peel the transfer tape from the wax paper, when you get to the center tape stop and just fold it over. Be care full not to stick the transfer tape to anything. Cut the wax paper.</p>
		
<p>4) Hold the clear transfer paper up and from the center place the squeegee on the vertical tape and squeegee out while holding the clear transfer tape up from the glass until the squeegee passes on it.</p>	<p>5) Keep working the squeegee out from the center till you have squeegee all of the decal on.</p>	<p>6) Remove the center masking tape and other tape holding the decal in place.</p>
		
<p>7) Peel the transfer tape from the wax paper, While holding the tarsier tape up place the squeegee on the center and squeegee your way out to the side.</p>	<p>8) Keep working the squeegee out from the center till you have squeegee all of the decal on.</p>	<p>9) After you squeegee all of the surface of the decal slowly peel the clear transfer tape off. Slowly ass you lift up look if the decal is lifting or staying on the glass. If their are bubbles just try to work them out with you fingers or poke it with a needle and press and work the air out.</p>